


CX / MX Semi / Full Cone



These nozzles produce a very fine atomisation using only hydraulic pressure resulting in a semi-full cone spray pattern.

They are used for humidification, dust control, odour control, air & gas washing, lubrication, and cooling.



CAP



CX



FILTER



BODY



CX




MX



MX FILTER


CX tips can be used with HG bodies and caps.

One-piece 1/4" threaded nozzles with threaded rear filter also available.



Construction

Constructed from brass or SS303.



Model	Ø1 mm	Flow lpm @ bar						Spray angle @ bar
		2	5	10	15	20	30	5
0.7	0.35	~	3.6	5.2	6.3	7.3	8.9	35
1	0.4	~	4.5	6.4	7.8	9.1	11.2	60
1.5	0.5	4.8	7.6	10.5	13.1	15.1	18.5	70
2	0.6	6.4	10.2	14.3	17.7	20.1	25.2	75
3	0.7	9.6	15.2	21.2	26.4	30.5	37.6	70
4	1.1	12.8	20.1	29.1	35.2	40.4	50.5	80
6	1.1	19.2	30.1	43.0	53.0	61.0	74.0	75
8	1.5	26.0	40.0	57.0	70.0	81.0	99.0	90
10	1.6	32.0	50.0	71.0	88.0	102	125	80
12	1.9	38.0	61.0	86.0	105	120	150	80
14	1.9	45.0	71.0	100	124	144	175	85
18	1.9	57.0	91.0	129	158	182	220	85
22	1.9	70.0	110	157	193	220	270	70
25	2.2	83.0	131	186	225	260	320	85