

PAPERJET

PAJS Sapphire tip spray nozzles



The PAJS is a sapphire tipped nozzle that is very hard wearing at high pressures. It has a precise 0° spray angle and is easy to install. It is used for felt & wire cleaning, paper trimming, high pressure washing and chemical etching.



Construction

Constructed of stainless steel with sapphire tip.

Model	Size Ø di mm	Flow rate @ bar G (water)							
		1	3	10	20	50	70	100	300
PAJS 0.6	0.6	0.17	0.29	0.53	0.74	1.21	1.45	1.68	2.91
PAJS 0.7	0.7	0.23	0.40	0.72	1.03	1.67	2.00	2.29	3.96
PAJS 0.9	0.9	0.38	0.65	1.19	1.67	2.71	3.25	3.78	6.54
PAJS 1	1.0	0.47	0.81	1.48	2.08	3.38	4.05	4.67	8.08
PAJS 1.2	1.1	0.56	0.98	1.79	2.51	4.08	4.90	5.64	9.78
PAJS 1.3	1.3	0.79	1.37	2.49	3.51	5.71	6.85	7.88	13.66
PAJS 1.5	1.5	1.05	1.82	3.32	4.67	7.58	9.10	10.50	18.18
PAJS 1.7	1.7	1.35	2.34	4.26	6.00	9.75	11.70	13.48	23.35
PAJS 1.8	1.9	1.66	2.92	5.33	7.49	12.17	14.60	16.84	29.17
PAJS 2.3	2.3	2.47	4.27	7.80	10.95	17.79	21.35	24.68	42.74
PAJS 2.8	2.8	3.68	6.33	11.57	16.23	26.38	31.65	36.57	63.35